



KEMPEROL® 1K-LF FLASHING *Waterproofing for Patching & Repairs*



NORTH AMERICAN HEADQUARTERS

Kemper System America, Inc.
1200 North America Drive
West Seneca, NY 14224
Tel: (716) 558-2971
Toll Free: (800) 541-5455
www.kempersystem.com

All information and statements contained herein are believed to be accurate, but Kemper System America, Inc., its agents and/or affiliates make no warranty with respect thereto, including but not limited to any results to be obtained or the infringement of any proprietary right. Improper and unauthorized use or application of such information or statements or the material or systems described herein is at user's sole discretion and risk, and consequently user acknowledges that Kemper System America, Inc. shall bear no responsibility or liability for same. Nothing herein shall be construed as a license of or recommendation for use which infringes any proprietary right. All sales are subject to Kemper System America, Inc.'s Standard Terms and Conditions of Sale, including but not limited to its Limited Warranty.

KEM-196 REV C JAN 23
Kemperol® 1K-LF Flashing Brochure
© Copyright 2023 Kemper System America, Inc.





PATCHING & REPAIRS

This single-component, UV-stable, low VOC, solvent-free, cold liquid-applied, silane based moisture-cure resin is reinforced with fleece and designed to assist in the patching, repairs and flashing elements of roofing and waterproofing systems.

The Kemperol® 1K-LF Flashing system is suitable for both interior and exterior applications. This high performance membrane system was designed for ease of application to difficult penetration fixtures and complex details:

Flashings • Skylights • Drains • Gutters • Repairs



ADVANTAGES:

HIGH HUMIDITY TOLERANCE: Can be used on slightly damp substrates & is rain resistant two hours after application.

EFFICIENT & DURABLE: This single-component silane-based system is designed for quick, durable roof repairs.

COST EFFECTIVE: No primer needed on most substrates & reusable: replace the lid and re-use at a later date.


READY-TO-USE: Just stir and apply straight from the can.

EASE OF USE: Cold liquid-applied with a brush or roller.

ODOR-FREE: Can be applied without disruption to occupied buildings.

The Kemperol® 1K-LF Flashing reinforced membrane system was designed for easy application under difficult circumstances such as application to damp surfaces, or where alkali resistance is required. No waiting time required, this resin is simply stirred & applied straight from the can to the substrate and is walkable within 16 hours of application.

Kemperol® 1K-LF Flashing comes in two fully-integrated colors:



Light Gray



Anthracite Gray