


# Excellence in Waterproofing, Roofing and Surfacing Technology

Our highly trained and professional staff stands behind our technology with a half-century of experience and expertise. If you have a challenging project that requires a built-to-last, peace of mind, long-term solution, contact Kemper System today.

## Your KEMPER SYSTEM Partner:



### KEMPER SYSTEM AMERICA, Inc.

1 Reuten Drive  
Closter, NJ 07624  
Tel: (201) 833-8898  
Toll Free: (800) 541-5455

[www.kempersystem.net](http://www.kempersystem.net)

### NORTH AMERICAN HEADQUARTERS

1200 North America Drive  
West Seneca, NY 14224  
Tel: (716) 558-2971

[inquiry@kempersystem.com](mailto:inquiry@kempersystem.com)

### KEMPER SYSTEM CANADA, Inc.

5200 Dixie Road, Suite 13  
Mississauga, ON L4W 1E4  
Canada  
Tel: (905) 624-5463

[www.kempersystem.ca](http://www.kempersystem.ca)



All information and statements contained herein are believed to be accurate, but Kemper System America, Inc., its agents and/or affiliates make no warranty with respect thereto, including but not limited to any results to be obtained or the infringement of any proprietary right. Improper and unauthorized use or application of such information or statements or the material or systems described herein is at user's sole discretion and risk, and consequently user acknowledges that Kemper System America, Inc. shall bear no responsibility or liability for same. Nothing herein shall be construed as a license of or recommendation for use which infringes any proprietary right. All sales are subject to Kemper System America, Inc.'s Standard Terms and Conditions of Sale, including but not limited to its Limited Warranty.

# KEMPEROL® 022

## Waterproofing for Interior Applications



Tiled wet rooms require waterproofing. This ensures long-term protection against moisture infiltration into the building's interior finishes. Ceramic tiles provide a robust wearing surface, but are never 100% waterproof. If this is not avoided, it may result in expensive repairs.

## Engineered in Germany

Kemperol 022 was developed in Germany and exceed the strict German regulations for interior waterproofing membranes. This solvent-free technology is now available in the North American market.

The advantages of KEMPEROL® 022 Waterproofing at a glance:

- ANSI A118.10 compliant
- Fleece reinforced
- Even layer thickness
- 2 mm joint spanning
- No sealer required
- 1.5 mm crack bridging
- Single layer, time saving application
- 40 mil / 1 mm membrane thickness



## KEMPEROL® 022 Waterproofing – the liquid system

Kemperol 022 is a solvent free, cold-liquid applied, reinforced waterproofing membrane with Kemperol 500 Fleece reinforcement. For most substrates such as concrete, wooden, cement boards, and metal surfaces primer is not required. For all other substrates please review the primer recommendation guidelines.

The waterproofing system is applied wet-on-wet in two coats (first coat – fleece reinforcement – second coat). The wet, uncured membrane is then to be covered with a broadcast of Kemperol Surfacing Sand or approved equal kiln-dried silica sand, size 18, at 30 lbs / 100 sq. ft. Once the membrane has cured ceramic tiles can be applied with an appropriate tile adhesive.

Kemperol 022 waterproofing membrane can be applied in wet room walls and floors with direct or indirect load and floor drainage. It is ideal for household shower pans and bathrooms as well as commercial hotel applications, kitchens, and any other wet room areas that require tile application.

The advantage of this waterproofing membrane system is that it can be applied in a single layer application. Providing an ease of installation for the contractor and owner which can expedite the tile project.

The cold-liquid applied technology utilized in this system was developed by Kemper System and has been proven for over 50 years in roofing and waterproofing applications. The system provides a seamless application, with the reinforcement that ensures a durable membrane that can bridge cracks and joints.