

Printing date 07/29/2019

Reviewed on 07/29/2019

## 1 Identification

- **Product identifier:** 200-77-101, 202-77-201
- **Trade name:** **KEMPEROL® BR M Waterproofing**
- **Item number(s):** 200-77-101, 202-77-201
- **SDS Number:** 135
- **Application of the substance / the mixture** ROOF COATING
- **Manufacturer/Supplier:**  
USA ADDRESS:

KEMPER SYSTEM AMERICA, INC.  
1200 NORTH AMERICA DR,  
WEST SENECA, NY 14224  
PH (716) 558-2971

CANADIAN ADDRESS:

KEMPER SYSTEM CANADA  
6345 NETHERHART ROAD  
MISSISSAUGA, ON L5T 1B8  
PH (905) 624-5463  
FAX (905) 624-2840

- **Information department:**  
Tel: (716) 558-2971 ext. 228  
[www.kempersystem.net](http://www.kempersystem.net)
- **Emergency telephone number:**  
ChemTrec (800) 424-9300 / 1-(703)-741-5970  
Canada only: CANUTEC (Call collect) (613) 996-6666

## 2 Hazard(s) identification

- **Classification of the substance or mixture:**



GHS02 Flame

Flammable Liquids - Category 3

H226 Flammable liquid and vapour.



GHS08 Health hazard

Respiratory Sensitizer - Category 1

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carcinogenicity – Category 2

H351 Suspected of causing cancer.

Reproductive Toxicity - Category 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure - Category 1  
H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irritation - Category 2

H315 Causes skin irritation.

Eye Irritation - Category 2A

H319 Causes serious eye irritation.

(Contd. on page 2)

CA

# Safety Data Sheet

## acc. to OSHA HCS & WHMIS

Printing date 07/29/2019

Reviewed on 07/29/2019

**Trade name:** KEMPEROL® BR M Waterproofing

(Contd. of page 1)

Skin Sensitizer - Category 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure -  
Category 3

H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Signal word:** Danger

- **Hazard-determining components of labeling:**

styrene

Aromatic polyisocyanate prepolymer

- **Hazard statements:**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

- **Precautionary statements:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P243 Take actions to prevent static discharges.

P260 Do not breathe mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P285 In case of inadequate ventilation wear respiratory protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P312 IF INHALED: Call a doctor if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, sand, extinguishing powder.

P403 Store in a well-ventilated place.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

-CA

# Safety Data Sheet

acc. to OSHA HCS & WHMIS

Printing date 07/29/2019

Reviewed on 07/29/2019

**Trade name:** KEMPEROL® BR M Waterproofing

(Contd. of page 2)

- **NFPA ratings (scale 0 - 4):**



Health = 2  
Fire = 3  
Reactivity = 0

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

100-42-5	styrene	10-30% w/w *
72088-97-2	Aromatic polyisocyanate prepolymer	≥0.1-<1% w/w *

\* Actual concentration ranges are withheld as a trade secret.

### 4 First-aid measures

- **General information:** Symptoms of poisoning may even occur after several hours.
- **After inhalation:**  
Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
- **After skin contact:**  
Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.
- **After eye contact:**  
Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists get medical advice/attention.
- **After swallowing:** Call a poison center/doctor if you feel unwell. Rinse mouth.
- **Most important symptoms and effects, both acute and delayed:**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed:**  
No further relevant information available.

### 5 Fire-fighting measures

- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture:** No further relevant information available.
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures:**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

CA

# Safety Data Sheet

acc. to OSHA HCS & WHMIS

Printing date 07/29/2019

Reviewed on 07/29/2019

**Trade name:** KEMPEROL® BR M Waterproofing

(Contd. of page 3)

- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- **Reference to other sections:**
  - See Section 7 for information on safe handling.
  - See Section 8 for information on personal protection equipment.
  - See Section 13 for disposal information.

## 7 Handling and storage

- **Handling**
- **Precautions for safe handling:**
  - Ensure good ventilation/exhaustion at the workplace.
  - Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
  - Keep ignition sources away - Do not smoke.
  - Protect against electrostatic charges.
- **Storage**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s):** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Components with limit values that require monitoring at the workplace:**

### 100-42-5 styrene

EL (Canada)	Short-term value: 75 ppm Long-term value: 50 ppm IARC 2B
EV (Canada)	Short-term value: 100 ppm Long-term value: 35 ppm
PEL (USA)	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs
REL (USA)	Short-term value: 425 mg/m <sup>3</sup> , 100 ppm Long-term value: 215 mg/m <sup>3</sup> , 50 ppm
TLV (USA)	Short-term value: (170) mg/m <sup>3</sup> , (40) ppm Long-term value: (85) NIC-8.5 mg/m <sup>3</sup> , (20) NIC-2 ppm BEI, NIC-A3, NIC-OTO

(Contd. on page 5)

CA

# Safety Data Sheet

acc. to OSHA HCS & WHMIS

Printing date 07/29/2019

Reviewed on 07/29/2019

**Trade name:** KEMPEROL® BR M Waterproofing

(Contd. of page 4)

· **Ingredients with biological limit values:**

**100-42-5 styrene**

BEI (USA)	400 mg/g creatinine Medium: urine Time: end of shift Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)
	0.2 mg/L Medium: venous blood Time: end of shift Parameter: Styrene (semi-quantitative)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Personal protective equipment**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Breathing equipment:** Use suitable respiratory protective device in case of insufficient ventilation.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves:**  
Fluorocarbon rubber (Viton)  
Nitrile rubber, NBR  
Natural rubber, NR
- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

- |   |                 |
|---|-----------------|
| · <b>Form:</b>                          | Liquid          |
| · <b>Color:</b>                         | Grey            |
| · <b>Odor:</b>                          | Characteristic  |
| · <b>Odor threshold:</b>                | Not determined. |
| · <b>pH-value:</b>                      | Not determined. |
| · <b>Change in condition</b>            |                 |
| <b>Melting point/Melting range:</b>     | Undetermined.   |
| <b>Boiling point/Boiling range:</b>     | 145 °C          |
| · <b>Flash point:</b>                   | 35 °C           |
| · <b>Flammability (solid, gaseous):</b> | Not determined. |

(Contd. on page 6)

CA

# Safety Data Sheet

acc. to OSHA HCS & WHMIS

Printing date 07/29/2019

Reviewed on 07/29/2019

**Trade name:** KEMPEROL® BR M Waterproofing

(Contd. of page 5)

· <b>Ignition temperature:</b>	480 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits</b>	
<b>Lower:</b>	1.2 Vol %
<b>Upper:</b>	8.9 Vol %
· <b>Vapor pressure at 20 °C:</b>	6 hPa
· <b>Density at 20 °C:</b>	1.16 g/cm <sup>3</sup>
· <b>Relative density:</b>	Not determined.
· <b>Vapor density:</b>	Not determined.
· <b>Evaporation rate:</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>VOC content:</b>	44 g/l
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects:**
- **Acute toxicity**

- **LD/LC50 values that are relevant for classification:**

### 100-42-5 styrene

Oral	LD50	5,000 mg/kg (rat)
Inhalative	LC50/4 h	24 mg/l (rat)

- **Specific symptoms in biological assay:** No further relevant information available.
- **Primary irritant effect**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

(Contd. on page 7)

CA

# Safety Data Sheet

acc. to OSHA HCS & WHMIS

Printing date 07/29/2019

Reviewed on 07/29/2019

**Trade name:** KEMPEROL® BR M Waterproofing

(Contd. of page 6)

- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

100-42-5 styrene

2B

- **NTP (National Toxicology Program)**

100-42-5 styrene

R

## 12 Ecological information

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Other adverse effects:** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings**
- **Recommendation:**  
Place in a sealed container and label as waste. Place in a safe area, and comply with all federal, state, provincial and local regulations for disposal.

## 14 Transport information

- |   |               |
|---|---------------|
| <ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, TDG, ADN, IMDG, IATA</b></li> </ul>  | Not regulated |
| <ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT, TDG, ADN, IMDG, IATA</b></li> </ul>                            | Not regulated |
| <ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT, TDG, ADN, IMDG, IATA</b></li> <li>· <b>Class</b></li> </ul> | Not regulated |

(Contd. on page 8)

CA

# Safety Data Sheet

acc. to OSHA HCS & WHMIS

Printing date 07/29/2019

Reviewed on 07/29/2019

**Trade name:** KEMPEROL® BR M Waterproofing

(Contd. of page 7)

- |   |                      |
|---|----------------------|
| · <b>Packing group</b><br>· <b>DOT, TDG, IMDG, IATA</b>                           | Not regulated        |
| · <b>Environmental hazards:</b><br>· <b>Marine pollutant:</b>                     | No                   |
| · <b>Special precautions for user:</b><br>· <b>Stowage Category</b>               | Not applicable.<br>A |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:</b> | Not applicable.      |
| · <b>UN "Model Regulation":</b>   | Not regulated        |

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

100-42-5 styrene

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed or exempted

- **Proposition 65**

- **Chemicals known to cause cancer:**

100-42-5 styrene

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Canadian substance listings**

- **Canadian Domestic Substances List (DSL/NDL):**

All ingredients are listed.

- **Canadian Ingredient Disclosure list (limit 0.1%):**

100-42-5 styrene

- **Canadian Ingredient Disclosure list (limit 1%):**

None of the ingredients is listed.

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)



# Safety Data Sheet

## acc. to OSHA HCS & WHMIS

Printing date 07/29/2019

Reviewed on 07/29/2019

**Trade name:** KEMPEROL® BR M Waterproofing

(Contd. of page 8)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

styrene

Aromatic polyisocyanate prepolymer

· **Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P243 Take actions to prevent static discharges.

P260 Do not breathe mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P285 In case of inadequate ventilation wear respiratory protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P312 IF INHALED: Call a doctor if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, sand, extinguishing powder.

P403 Store in a well-ventilated place.

P405 Store locked up.

(Contd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS & WHMIS

Printing date 07/29/2019

Reviewed on 07/29/2019

**Trade name:** KEMPEROL® BR M Waterproofing

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. of page 9)

## 16 Other information

This SDS format meets ANSI Z400.1-2010, OSHA 1910.1200 and WHMIS requirements. Kemper System America, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Product use and conditions of use are beyond the control of Kemper System America, Inc. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test results is the responsibility of end-user. No other warranties, expressed or implied, are made. Kemper System America, Inc is an ISO 9001:2015 and ISO 14001:2015 registered company.

- **Department issuing SDS:** Product safety department
- **Contact:** Stephen Nowicki
- **Date of the latest revision of the safety data sheet** 07/29/2019 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent

CA